

Airborne Lidars to Measure Stratospheric Winds and Temperatures over Deep Convection during the CGWaveS Campaign

Bifford P. Williams

Global Atmospheric Technologies and Sciences (GATS)

Session 12 - Measurements in the stratosphere, mesosphere and thermosphere
Wednesday, 12:00
Poster 12

Acknowledgements: CGWaveS is funded by NSF AGS-2017263 and supported by NCAR EOL/RAF. The original lidar development was funded by NSF AGS-1261619 and the data examples from DEEPWAVE were funded by AGS-1338655.

References:

Dörnbrack, A., Eckermann, S. D., Williams, B. P., and Haggerty, J. (2022). Stratospheric Gravity Waves Excited by a Propagating Rossby Wave Train—A DEEPWAVE Case Study, Journal of the Atmospheric Sciences, 79(2), 567-591.

Huang, W., X. Chu, B. P. Williams, S. D. Harrell, J. Wiig, and C.-Y. She, Na Double-Edge Magneto-Optic Filter for Na Lidar Profiling of Wind and Temperature in the Lower Atmosphere, Optics Letters, 34, 199-201, 2009.

Williams, B. P. and S. Tomczyk, Magneto-optic Doppler analyzer: A new instrument to measure mesopause winds, Applied Optics, 35, 6494--6503, 1996.

The 30th International Laser Radar Conference (ILRC) virtual conference, June 26th – July 1st, 2022.

CGWaveS Campaign



- **CGWaveS:** Convective Gravity Waves in the Stratosphere, June/July 2023 in midwestern USA
- Thunderstorms and other convective systems produce convective gravity waves (CGWs) which have major influences on stratospheric circulation, structure, variability, and predictability
- Goal: Measure CGW generation, propagation, and variability in the stratosphere
- Method: Fly NCAR HIAPER Gulfstream V aircraft over large thunderstorms at night
- Instruments: Two lidars, aircraft in situ, OH imagers, and groundbased instruments.
- WRF, MAGIC, and CGCAM models will provide forecasts and context (Figure at right)
- Airborne lidars were developed at GATS for the DEEPWAVE campaign in 2014 over New Zealand




Figure 13. MAGIC simulation of CGWs employing the NEXRAD rainfall rate SA15 forcing at 2- km resolution over the CGWaveS RAO on 8 July 2016 at 15, 30, and 60 km, and in the x-z plane.

The 30th International Laser Radar Conference (ILRC) virtual conference, June 26th - July 1st, 2022.

Airborne Rayleigh Lidar



- Both lidars fit in two standard NCAR Gulfstream V instrument racks (right)
- Transmitter: diode-pumped Nd:YLF Photonics DS20-351, 5W, 1kHz, 351nm wavelength (bottom)
- Reason for UV instead of higher power green:
 - Eye safe at aircraft exit for overflying aircraft
 - Stronger Rayleigh scatter in UV
 - Less atmospheric absorption flying at ~14km
- Receiver: 0.4m Newtonian fiber coupled receiver
 - upgraded from $0.3 \text{ m} \rightarrow 75\%$ more signal than DEEPWAVE





The 30th International Laser Radar Conference (ILRC) virtual conference, June 26th - July 1st, 2022.

Airborne Rayleigh Lidar Example Data




Flight Mean Temp. (K

240


Hours (UT) Lidar: black, ECMWF: blue

260

Aerosol layers: 15-25km altitude at 200m horizontal and 37.5m altitude resolution



Density and temperature: 30-70km altitude, 3-12km horizontal and 1-2km vertical resolution, example below showing waves in temperature over the ocean near Antarctica on 18 July 2014 (see Dörnbrack et al., 2022).





The 30th International Laser Radar Conference (ILRC) virtual conference, June 26th – July 1st, 2022.

Airborne sodium wind-temperature lidar



- 10W Toptica DL-RFA-SHG CW laser externally pulsed into two 150mW beams
- 589nm, 10 MHz linewidth, 2MHz absolute frequency accuracy, 1kHz pulse repetition rate
- Laser scanned and locked to 3 frequencies using acousto-optic saturation vapor spectroscopy
- Zenith beam shares 0.4m Rayleigh telescope -> temperatures and vertical winds from 80-100km altitude
- Second 0.4m telescope points 20deg off zenith to get winds, temperatures and BSR ahead of aircraft from 18-30km and 80-100km






The 30th International Laser Radar Conference (ILRC) virtual conference, June 26th - July 1st, 2022.


Stratospheric winds from sodium vapor double-edge magneto-optic filter (DEMOF)



- Measures radial wind, temperature, and aerosol backscatter ratio from the Rayleigh/Mie scatter from the inclined Na beam from ~18-30km altitude
- The DEMOF was first developed at NCAR (Williams and Tomczyk, 1996) and at CU (Huang et al., 2009).
- The Wisconsin HSRL is a similar airborne lidar that uses an iodine absorption line to study aerosol backscatter.
- Uses a longitudinal magnetic field in a sodium vapor cell to Zeeman split the Na absorption line into two absorption lines coded by polarization
- The edge of the two absorption lines act as the "double-edge" to measure the Doppler shift of the returned light
- We switch the laser to two other frequencies to measure temperature and BSR with lower sensitivity
- DEMOF is less sensitive to vibrations than etalon-based systems







The 30th International Laser Radar Conference (ILRC) virtual conference, June 26th – July 1st, 2022.