

The 30th International Laser Radar Conference

Presentation ID: *Monday_ 03_P01*

Development of the Dual-wavelength Mie-Raman Lidar for Weather Modification Application


Yuquan Zhou⁽¹⁾, Yue Tao⁽¹⁾, Shuai Zhang⁽²⁾, Qibing Shi⁽²⁾, Weiyu Xu⁽²⁾, Jietai Mao⁽³⁾, <u>Dong Liu</u>^{(4)*}

- (1) CMA Weather Modification Centre, Beijing 10081, China
- (2) Hefei CAS GBQTech Co.,Ltd. Hefei, Anhui 230094, China
 - (3) Peking University, Beijing 100091, China
- (4) Key Laboratory of Atmospheric Optics, Anhui Institute of Optics and Fine Mechanics, Chinese Academy of Sciences, Hefei, Anhui 230031, China


2022. 6. 27

Lidar system development





Lidar photo and diagram



> Dual-wavelength Mie-Raman lidar

- 355/532nm two wavelengths transmitting
- 355,532p,532s,607nm four receiving channels

Two CCD Cameras

- 355nm/532nm overlap function correction
- Weather station and visibility meter
 - Temperature, humidity, visibility near-end calibration



Lidar main specifications

Laser transition unit:

- ✓ type: Inlite II-20
- ✓ wavelength: 355nm&532nm
- ✓ energy: ≥ 80mJ (532nm), ≥ 25mJ
 (355nm)
- ✓ Pulse duration: <8ns</p>
- ✓ repetition: 20Hz
- √ divergance: <0.5mrad(after expansion)
 </p>

Receiving unit:

- √ telescope: Cassegrain (16 inch)
- ✓ channels: 355nm, 532nm (p, s), 607nm
- ✓ detectors: PMT
- ✓ Data acquisition: AD 16bit
- √ Vertical resolution: 7.5-300m (adjustable)
- ✓ Time resolution:1-30min(adjustable)


Auxiliary equipment:

- ✓ CCD side-scattering Camera: 355nm, 532nm
- ✓ Weather station: wind, humidity, temperature, pressure
- ✓ Visibility meter: visibility

Data products:

- ✓ Max range: 20km(nightime); 4km(daytime,Mie);1.5km(daytime, Raman)
- ✓ Five profiles: extinction coefficient, backscattering coefficient, lidar ratio, size distribution(effective radius), depolarization ratio
- ✓ Two heights: cloud base height; atmosphere boundary layer height


Overlap function correction



Near-end calibration can be applied after Overlap function correction

Extinction coefficient retrieval before(up) and after (down) overlap function correction, respectively


Near-end retrieval case



Far-end retrieval, affected by clouds
Two problems: Far-end calibration and cloud

lidar ratio

Vis45m: visibility convert from lidar retrieved extinction coefficient at 45m height VisGround: directly measured visibility




Near-end retrieval, good performance under clouds



Effective radius retrieval

Two-wavelength retrieval technique






Taking the advantage of the linear relationship between effective radius(x-axis) and the rate of extinction/backscattering coefficient (y-axis) of the two wavelengths


Presentation ID: Thursday _ 03_29, Benli Liu

550nm/8.6mm



The protentional of cloud droplet radius retrieval combined lidar and millimeter radar(x-axis: water droplet effective radius; y-axis: the rate of extinction coefficient of 550nm and 8.6mm)

Aerosol and cloud classification



A simple scheme for lidar operators to fast distinguish the aerosol and cloud type.



Three lidar systems have been built and deployed in different sites. More data will be investigated.

Thanks for your attention!

