

Agreement and availability of Doppler velocity measurements from

co-located Doppler Wind Lidar and X-band weather radar

Jenna Ritvanen^{1,2}, Ewan O'Connor¹, Dmitri Moisseev^{1,2}, **Ludovic Thobois**³, Raisa Lehtinen⁴, Jani Tyynelä¹

Contact: jenna.ritvanen@fmi.fi / ludovic.thobois@vaisala.com

¹Finnish Meteorological Institute, Helsinki, Finland ²INAR, University of Helsinki, Helsinki, Finland ³Vaisala France SAS, Paris-Saclay, France ⁴Vaisala Oyj, Vantaa, Finland


04.Synergistic use of multiple instruments and techniques, networks and campaigns
27 June 2022
Monday 04 P02

Introduction



 Measurement campaign in Vantaa, Finland from May 2021 to November 2021


- Instruments
 - Vaisala WindCube400S Doppler lidar
 - Vaisala WRS400 X-band weather radar
- Aim to quantify differences in measurement performance in different conditions:
 - → Horizontal visibility
 - → Cloud base height
 - → Precipitation intensity
- The work was funded through the MWS-A project funded by the European Space Agency (4000132768/20/UK/ND).




Data availability during the entire campaign

Case examples






Thunderstorm/ precipitation



Clear air, no insects, horizontal visibility > 60km



Clear air, insects, horizontal visibility ~45km

Agreement of Doppler velocity measurements




- Radial velocity measurements interpolated to a common Cartesian grid for comparison.
- Measurements have good agreement:

$$\rightarrow$$
 R2 = 0.96

$$\rightarrow$$
 RMSD = 1.31 m/s

$$\rightarrow$$
 ME = -0.047 m/s

• Some artefacts visible that suggest using clutter filtering for Doppler lidar might be necessary.




Data availability as function of horizontal visibility



Doppler lidar has

- → low data availability in low visibility conditions.
- → highest data availability when horizontal visibility is 40-50km.

X-band radar has high data availability in conditions with low horizontal visibility.




Data availability as function of cloud base height



Doppler lidar cannot measure past cloud base.

X-band radar has best data availability in low cloud base height conditions.



Data availability as function of precipitation intensity



Precipitation intensity: Vaisala FS11P sensor as 10 min average

Doppler lidar: any precipitation indicates low data availability beyond first kilometers in range.

X-band radar: any precipitation indicates high data availability.

